



E-PACE

TECHNICAL SPECIFICATION
MAY 2021



E-PACE - TECHNICAL SPECIFICATION

POWERTRAIN	DIESEL		DIESEL MHEV	
	D165	D165	D165	D200
Mild Hybrid Electric Vehicle (MHEV)	-	■	■	■
Transmission	Manual	Automatic	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Front Wheel Drive (FWD)	FWD	AWD	AWD	AWD
Maximum power (PS/kW/rpm)	163/120/3.750	163/120/3.750	163/120/3.750	204/150/3.750
Maximum torque (Nm/rpm)	380/1.500-2.500	380/1.500-2.500	380/1.500-2.500	430/1.750-2.500
Capacity (cc)	1.997	1.997	1.997	1.997
No. of cylinders/Valves per cylinder	4/4	4/4	4/4	4/4
Cylinder layout	In-line	In-line	In-line	In-line
Bore/stroke (mm)	83/92,31	83/92,31	83/92,31	83/92,31
Compression ratio (:1)	16,5+/-0,5	16,5+/-0,5	16,5+/-0,5	16,5+/-0,5
PERFORMANCE				
Acceleration (secs) 0-100 km/h (0-60mph)	10 (9,5)	9,8 (9,2)	9,8 (9,2)	8,4 (7,9)
Maximum speed km/h (mph)	206 (128)	200 (124)	200 (124)	211 (131)
BRAKES				
Front type	17" wheels - Single Piston Sliding Caliper, Vented Disc 18" - 21" wheels - Twin Piston Sliding Caliper, Vented Disc		Twin Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	17" wheels - 325 18" - 21" wheels - 349		349	
Rear type	Single Piston Sliding Caliper, Solid Disc		Single Piston Sliding Caliper, Solid Disc	
Rear diameter (mm)	300	300	300	300
Park Brake	Integrated motor-on caliper		Integrated motor-on caliper	

■ Standard - Not available.

Some features on images may vary between optional and standard for different model years and due to the impact of Covid-19, many of our images have not been updated to reflect 22MY specifications. Please refer to the car configurator and additionally consult your local Retailer for detailed 22MY specifications and do not base an order on website imagery alone. Jaguar Land Rover Limited is constantly seeking ways to improve the specification, design and production of its vehicles, parts and accessories and alterations take place continually, and we reserve the right to change without notice.

E-PACE – TECHNICAL SPECIFICATION

	DIESEL		DIESEL MHEV	
	D165	D165	D200	
WEIGHTS (kg)*				
Unladen weight (EU)**	1.809	1.916	1.952	
Unladen weight (DIN)†	1.734	1.841	1.877	
Gross Vehicle Weight (GVW)	2.360	2.470	2.470	
TOWING (kg)				
Unbraked trailer	750	750	750	
Maximum towing	1.600	1.800	2.000 (EU & ROW)/1.800 (AUS)	
Maximum coupling point (nose weight)	100	100	100	
Maximum vehicle and trailer combination	3.960	4.270	4.470 (EU & ROW)/4.270 (AUS)	
ROOF CARRYING (kg)				
Maximum roof load (including cross bars)	75	75	75	

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE - TECHNICAL SPECIFICATION

FUEL ECONOMY			DIESEL		DIESEL MHEV			
			D165	D165	D165		D200	
Fuel tank capacity - useable litres	Large		65		65		65	
	Eco		54		54		54	
Diesel Particulate Filter (DPF)			■		■		■	
NEDC EQUIVALENT (NEDC2)*			Class A	Class B	Class A	Class B	Class A	Class B
Driveline			FWD		AWD		AWD	
NEDC2 Consumption	Urban	l/100km (mpg)	5,6 (50,4)	5,9 (47,9)	6,0 (47,1)	6,2 (45,6)	6,0 (47,1)	6,2 (45,6)
	Extra Urban	l/100km (mpg)	4,6 (61,4)	5,1 (55,4)	4,9 (57,6)	5,0 (56,5)	4,9 (57,6)	5,0 (56,5)
	Combined	l/100km (mpg)	5,0 (56,5)	5,4 (52,3)	5,2 (54,3)	5,4 (52,3)	5,3 (53,3)	5,4 (52,3)
NEDC2 CO ₂ Emissions	Urban	(g/km)	147	154	158	162	159	163
	Extra Urban	(g/km)	122	133	128	132	128	133
	Combined	(g/km)	131	141	139	143	140	144
WLTP**								
WLTP Consumption	Low	l/100km (mpg)	7,6-8,3 (37,2-34,0)		7,3-7,8 (38,7-36,2)		7,4-7,8 (38,2-36,2)	
	Medium	l/100km (mpg)	6,0-6,9 (47,1-40,9)		6,5-7,1 (43,5-39,8)		6,6-7,2 (42,8-39,2)	
	High	l/100km (mpg)	5,2-5,9 (54,3-47,9)		5,6-6,1 (50,4-46,3)		5,6-6,2 (50,4-45,6)	
	Extra High	l/100km (mpg)	6,2-7,0 (45,6-40,4)		6,7-7,2 (42,2-39,2)		6,7-7,4 (42,2-38,2)	
	Combined	l/100km (mpg)	6,0-6,8 (47,1-41,5)		6,4-6,9 (44,1-40,9)		6,4-7,0 (44,1-40,4)	
WLTP CO ₂ Emissions	Low	(g/km)	198-218		191-204		193-204	
	Medium	(g/km)	157-180		171-187		173-189	
	High	(g/km)	137-155		146-160		147-162	
	Extra High	(g/km)	161-184		175-189		176-194	
	Combined	(g/km)	158-179		167-182		169-185	

■ Standard.

Class A (17"-20" wheels and 19" wheels with Summer tyres). Class B (19" wheels with All-Season tyres and 21" wheels).

*The figures provided are NEDC2 calculated from official manufacturer's WLTP tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. NEDC2 are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied.

**The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

E-PACE - TECHNICAL SPECIFICATION

	DIESEL	
POWERTRAIN	D165	D200
Mild Hybrid Electric Vehicle (MHEV)	-	-
Transmission	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Front Wheel Drive (FWD)	AWD	AWD
Maximum power (PS/kW/rpm)	163/120/3.750	199/146/3.750
Maximum torque (Nm/rpm)	380/1.500-2.500	430/1.750-2.500
Capacity (cc)	1.997	1.997
No. of cylinders/Valves per cylinder	4/4	4/4
Cylinder layout	In-line	In-line
Bore/stroke (mm)	83/92,31	83/92,31
Compression ratio (:1)	16,5+/-0,5	16,5+/-0,5
PERFORMANCE		
Acceleration (secs) 0-100 km/h (0-60mph)	9,8 (9,2)	8,4 (7,9)
Maximum speed km/h (mph)	200 (124)	211 (131)
BRAKES		
Front type	17" wheels - Single Piston Sliding Caliper, Vented Disc 18" - 21" wheels - Twin Piston Sliding Caliper, Vented Disc	Twin Piston Sliding Caliper, Vented Disc
Front diameter (mm)	17" wheels - 325 18" - 21" wheels - 349	349
Rear type	Single Piston Sliding Caliper, Solid Disc	Single Piston Sliding Caliper, Solid Disc
Rear diameter (mm)	300	300
Park Brake	Integrated motor-on caliper	Integrated motor-on caliper

E-PACE - TECHNICAL SPECIFICATION

	DIESEL	
WEIGHTS (kg)*	D165	D200
Unladen weight (EU)**	1.884	1.920
Unladen weight (DIN)†	1.809	1.845
Gross Vehicle Weight (GVW)	2.470	2.470
TOWING (kg)		
Unbraked trailer	750	750
Maximum towing	1.800	2.000 (EU)/1.800 (AUS)
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.270	4.470 (EU & ROW)/4.270 (AUS)
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	75	75

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE - TECHNICAL SPECIFICATION

			DIESEL	
FUEL ECONOMY			D165	D200
Fuel tank capacity - useable litres	Large		65	65
Diesel Particulate Filter (DPF)			■	■
Driveline			AWD	AWD
Consumption	Combined	l/100km (mpg)	TBC	TBC
CO ₂ Emissions	Combined	(g/km)	TBC	TBC

E-PACE - TECHNICAL SPECIFICATION

POWERTRAIN	PETROL MHEV		
	P160	P200	P250
Mild Hybrid Electric Vehicle (MHEV)	■	■	■
Transmission	Automatic	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Front Wheel Drive (FWD)	FWD	AWD	AWD
Maximum power (PS/kW/rpm)	160/118/5.500	200/147/5.500	249/184/5.500
Maximum torque (Nm/rpm)	260/1.600-4.000	320/1.200-4.000	365/1.300-4.500
Capacity (cc)	1.498	1.997,34	1.997,34
No. of cylinders/Valves per cylinder	3/4	4/4	4/4
Cylinder layout	In-line	In-line	In-line
Bore/stroke (mm)	83/92,29	83/92,29	83/92,29
Compression ratio (:1)	10,5+/-0,5	10,5+/-0,5	10,5+/-0,5
PERFORMANCE			
Acceleration (secs) 0-100 km/h (0-60mph)	10,3 (9,7)	8,5 (8,0)	7,5 (7,0)
Maximum speed km/h (mph)	197 (122)	212 (132)	229 (142)
BRAKES			
Front type	17" wheels - Single Piston Sliding Caliper, Vented Disc 18" - 21" wheels - Twin Piston Sliding Caliper, Vented Disc		Twin Piston Sliding Caliper, Vented Disc
Front diameter (mm)	17" wheels - 325 18" - 21" wheels - 349		349
Rear type	Single Piston Sliding Caliper, Solid Disc		Single Piston Sliding Caliper, Vented Disc
Rear diameter (mm)	300		325
Park Brake	Integrated motor-on caliper		Integrated motor-on caliper

E-PACE – TECHNICAL SPECIFICATION

	PETROL MHEV		
WEIGHTS (kg)*	P160	P200	P250
Unladen weight (EU)**	1.783	1.847	1.889
Unladen weight (DIN)†	1.708	1.772	1.814
Gross Vehicle Weight (GVW)	2.300	2.430	2.430
TOWING (kg)			
Unbraked trailer	-	750	750
Maximum towing	-	1.800	1.800
Maximum coupling point (nose weight)	-	100	100
Maximum vehicle and trailer combination	-	4.230	4.230
ROOF CARRYING (kg)			
Maximum roof load (including cross bars)	75	75	75

- Not available.

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE - TECHNICAL SPECIFICATION

FUEL ECONOMY			PETROL MHEV								
			P160		P200		P250				
Fuel tank capacity - useable litres			67		67		67				
Diesel/Gasoline Particulate Filter (DPF/GPF)			■		■		■				
NEDC EQUIVALENT (NEDC2)*			Class A		Class B		Class A		Class B		
Driveline			FWD			AWD			AWD		
NEDC2 Consumption	Urban	l/100km (mpg)	8,1 (34,9)	8,1 (34,9)	10,3 (27,4)	10,5 (26,9)	10,3 (27,4)	10,5 (26,9)			
	Extra Urban	l/100km (mpg)	6,0 (47,1)	6,0 (47,1)	6,2 (45,6)	6,4 (44,1)	6,3 (44,8)	6,5 (43,5)			
	Combined	l/100km (mpg)	6,8 (41,5)	6,8 (41,5)	7,7 (36,7)	7,9 (35,8)	7,7 (36,7)	7,9 (35,8)			
NEDC2 CO ₂ Emissions	Urban	(g/km)	185	185	233	237	234	238			
	Extra Urban	(g/km)	136	136	141	146	141	146			
	Combined	(g/km)	154	154	175	179	175	180			
WLTP**											
WLTP Consumption	Low	l/100km (mpg)	10,1-10,3 (28,0-27,4)			11,9-12,6 (23,7-22,4)			11,9-12,6 (23,7-22,4)		
	Medium	l/100km (mpg)	7,7-8,1 (36,7-34,9)			8,8-9,5 (32,1-29,7)			8,8-9,5 (32,1-29,7)		
	High	l/100km (mpg)	6,7-7,0 (42,2-40,4)			7,6-8,3 (37,2-34,0)			7,6-8,3 (37,2-34,0)		
	Extra High	l/100km (mpg)	8,4-8,9 (33,6-31,7)			8,9-9,9 (31,7-28,5)			8,9-9,9 (31,7-28,5)		
	Combined	l/100km (mpg)	8,0-8,3 (35,3-34,0)			8,9-9,7 (31,7-29,1)			8,9-9,7 (31,7-29,1)		
WLTP CO ₂ Emissions	Low	(g/km)	229-232			268-284			269-284		
	Medium	(g/km)	173-182			197-215			198-215		
	High	(g/km)	150-157			171-187			171-187		
	Extra High	(g/km)	189-199			200-222			201-222		
	Combined	(g/km)	179-187			200-218			200-218		

■ Standard.

Class A (17"-20" wheels and 19" wheels with Summer tyres). Class B (19" wheels with All-Season tyres and 21" wheels).

*The figures provided are NEDC2 calculated from official manufacturer's WLTP tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. NEDC2 are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied.

**The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

E-PACE - TECHNICAL SPECIFICATION

	PETROL	
	P200	P250
POWERTRAIN		
Mild Hybrid Electric Vehicle (MHEV)	-	-
Transmission	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Front Wheel Drive (FWD)	AWD	AWD
Maximum power (PS/kW/rpm)	200/147/5.500	249/184/5.500
Maximum torque (Nm/rpm)	320/1.200-4.000	365/1.300-4.500
Capacity (cc)	1.997,34	1.997,34
No. of cylinders/Valves per cylinder	4/4	4/4
Cylinder layout	In-line	In-line
Bore/stroke (mm)	83/92,29	83/92,29
Compression ratio (:1)	10,5+/-0,5	10,5+/-0,5
PERFORMANCE		
Acceleration (secs) 0-100 km/h (0-60mph)	8,5 (8,0)	7,5 (7,0)
Maximum speed km/h (mph)	212 (132)	229 (142)
BRAKES		
Front type	17" wheels - Single Piston Sliding Caliper, Vented Disc 18" - 21" wheels - Twin Piston Sliding Caliper, Vented Disc	Twin Piston Sliding Caliper, Vented Disc
Front diameter (mm)	17" wheels - 325 18" - 21" wheels - 349	349
Rear type	Single Piston Sliding Caliper, Solid Disc	Single Piston Sliding Caliper, Vented Disc
Rear diameter (mm)	300	325
Park Brake	Integrated motor-on caliper	Integrated motor-on caliper

E-PACE - TECHNICAL SPECIFICATION

	PETROL	
WEIGHTS (kg)*	P200	P250
Unladen weight (EU)**	1.815	1.857
Unladen weight (DIN)†	1.740	1.782
Gross Vehicle Weight (GVW)	2.430	2.430
TOWING (kg)		
Unbraked trailer	750	750
Maximum towing	1.800	1.800
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.230	4.230
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	75	75

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE - TECHNICAL SPECIFICATION

			PETROL	
FUEL ECONOMY			P200 [1]	P250 [1]
Fuel tank capacity - useable litres			67	67
Gasoline Particulate Filter (GPF)			■	■
Driveline				
Consumption	Combined	l/100km (mpg)	7,8	7,8
CO ₂ Emissions	Combined	(g/km)	180	180

■ Standard.

[1] The figures provided are NEDC calculated from official manufacturer's tests. Figures may vary according to environment and driving style. For comparison purposes only. Real-world figures may differ.

E-PACE - TECHNICAL SPECIFICATION

	PETROL MHEV	PETROL PHEV
	P300	P300e
POWERTRAIN		
Mild Hybrid Electric Vehicle (MHEV)	■	-
Transmission	Automatic	Automatic
Driveline: All Wheel Drive (AWD)	AWD	AWD
Maximum power (PS/kW/rpm)	300/221/5.500	309/227/5.500*
Maximum torque (Nm/rpm)	400/1.500-4.500	540/1.600-4.500*
Capacity (cc)	1.997,34	1.498
No. of cylinders/Valves per cylinder	4/4	3/4
Cylinder layout	In-line	In-line
Bore/stroke (mm)	83/92,29	83/92,29
Compression ratio (:1)	10,5+/-0,5	10,5+/-0,5
PERFORMANCE		
Acceleration (secs) 0-100 km/h (0-60mph)	6,9 (6,6)	6,5 (6,1)
Maximum speed km/h (mph)	241 (150)	216 (134)
ELECTRIC MOTOR DATA		
Maximum power (PS/kW)	-	109/80
Maximum torque (Nm)	-	260
BRAKES		
Front type	Twin Piston Sliding Caliper, Vented Disc	Twin Piston Sliding Caliper, Vented Disc
Front diameter (mm)	349	349
Rear type	Single Piston Sliding Caliper, Vented Disc	Single Piston Sliding Caliper, Vented Disc
Rear diameter (mm)	325	325
Park Brake	iEPB, motor on caliper	iEPB, motor on caliper

■ Standard - Not available.

*When combined with electric motor.

E-PACE – TECHNICAL SPECIFICATION

	PETROL MHEV	PETROL PHEV
WEIGHTS (kg)*	P300	P300e
Unladen weight (EU)**	1.952	2.173
Unladen weight (DIN)†	1.877	2.098
Gross Vehicle Weight (GVW)	2.450	2.670
TOWING (kg)		
Unbraked trailer	750	750
Maximum towing	1.800	1.600 (EU)/1.500 (ROW)
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.250	4.270 (EU)/4.170 (ROW)
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	75	75

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE - TECHNICAL SPECIFICATION

			PETROL MHEV		PETROL PHEV	
FUEL ECONOMY			P300		P300e	
Fuel tank capacity - useable litres			67		57,6	
Gasoline Particulate Filter (GPF)			■		■	
EV Range Class A Combined (NEDC2*) km (miles)			-		68 (42)	
EV Range TEH Combined (WLTP**) km (miles)			-		55 (34)	
NEDC EQUIVALENT (NEDC2)*			Class A		Class B	
Driveline			AWD		AWD	
NEDC2 Consumption	Urban	l/100km (mpg)	9,5 (29,7)	9,9 (28,5)	-	-
	Extra Urban	l/100km (mpg)	6,6 (42,8)	6,7 (42,2)	-	-
	Combined	l/100km (mpg)	7,7 (36,7)	7,9 (35,8)	2,0 (141)	2,0 (141)
NEDC2 CO ₂ Emissions	Urban	(g/km)	217	226	-	-
	Extra Urban	(g/km)	150	153	-	-
	Combined	(g/km)	175	179	43	45
WLTP**						
WLTP Consumption	Low	l/100km (mpg)	12,1-12,4 (23,3-22,8)		-	
	Medium	l/100km (mpg)	9,1-9,7 (31,0-29,1)		-	
	High	l/100km (mpg)	7,6-8,3 (37,2-34,0)		-	
	Extra High	l/100km (mpg)	9,1-9,9 (31,0-28,5)		-	
	Combined	l/100km (mpg)	9,0-9,7 (31,4-29,1)		2,0 (141,3)	
WLTP CO ₂ Emissions	Low	(g/km)	273-279		-	
	Medium	(g/km)	205-219		-	
	High	(g/km)	172-187		-	
	Extra High	(g/km)	204-223		-	
	Combined	(g/km)	204-218		44	

■ Standard - Not available.

Class A (17"-20" wheels and 19" wheels with Summer tyres). Class B (19" wheels with All-Season tyres and 21" wheels).

*The figures provided are NEDC2 calculated from official manufacturer's WLTP tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. NEDC2 are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

E-PACE - DIMENSIONS

Vehicle Height - 1.648m

Headroom

Maximum front/rear headroom

With Fixed metal roof fitted 976/974mm

With Panoramic roof fitted 996/970mm

Legroom

Maximum front legroom (Manual) 1.018m

Maximum front legroom (Automatic) 1.030m

Maximum rear legroom 872mm

Loadspace Capacity

Height 705mm, Width 1.311m

Loadspace width between arches 1.057m

Maximum loadspace volume behind first row

Dry* 1.170 litres, Wet** 1.386 litres

Maximum loadspace volume behind second row

Dry* 494 litres, Wet** 601 litres

Turning Circle

Kerb-to-kerb 11.63m

Wall-to-wall 12m

Turns lock-to-lock 2,31

Overall Width
(inc. mirrors) 2.088m
(mirrors folded) 1.984m



17" - 18" wheels - 1625mm
19" - 21" wheels - 1635mm



17" - 18" wheels - 1624mm
19" - 21" wheels - 1634mm



2.681m



4.395m

*Dry: Volume as measured with VDA-compliant solid blocks (200mm x 50mm x 100mm).

**Wet: Volume as measured by simulating the loadspace filled with liquid.

Dimensions were measured with vehicle at unladen weight.