

XF

JAGUAR

# XF SALOON - TECHNICAL SPECIFICATION

<b>POWERTRAIN</b>	<b>D200 MHEV</b>	
Transmission	Automatic	
Driveline: All Wheel Drive (AWD) or Rear Wheel Drive (RWD)	RWD	AWD
Maximum power (PS (kW) / rpm)	204 (150) / 3.750	204 (150) / 3.750
Maximum torque (Nm / rpm)	430 / 1.750-2.500	430 / 1.750-2.500
Capacity (cc)	1.998	1.998
No. of cylinders / Valves per cylinder	4 / 4	4 / 4
Cylinder layout	Inline	Inline
Bore / stroke (mm)	83 / 92.3	83 / 92.3
Compression ratio (+/-0.5)	16.5	16.5
<b>PERFORMANCE</b>		
Acceleration (secs) 0-100 km/h (0-60mph)	7,6 (7,1)	7,8 (7,3)
Maximum speed km/h (mph)	235 (146)	230 (143)
<b>BRAKES</b>		
Front type	Single Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	325	325
Rear type	Single Piston Sliding Caliper, Vented Disc	
Rear diameter (mm)	325	325
Park Brake	iEPB, motor on caliper	

Some features on images may vary between optional and standard for different model years and due to the impact of Covid-19, many of our images have not been updated to reflect 24MY specifications. Please refer to the car configurator and additionally consult your local Retailer for detailed 24MY specifications and do not base an order on website imagery alone. Jaguar Land Rover Limited is constantly seeking ways to improve the specification, design and production of its vehicles, parts and accessories and alterations take place continually, and we reserve the right to change without notice.

# XF SALOON - TECHNICAL SPECIFICATION

<b>WEIGHTS (kg)*</b>	<b>D200 MHEV</b>	
Unladen weight (EU)**	1.810	1.869
Unladen weight (DIN)†	1.735	1.794
Gross Vehicle Weight (GVW)	2.350	2.410
<b>TOWING (kg)</b>		
Unbraked trailer	750	750
Maximum towing	2.000	2.000
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.350	4.410
<b>ROOF CARRYING (kg)</b>		
Maximum roof load (including cross bars)	75	75

\*Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

# XF SALOON - TECHNICAL SPECIFICATION

## FUEL ECONOMY

Fuel tank capacity - useable litres	<b>D200 MHEV</b>	68
Diesel/Gasoline Particulate Filter (DPF/GPF)		■

## WLTP\*

Driveline			RWD	AWD
WLTP Consumption	Low	l/100km (mpg)	6,5-6,9 (43,5-40,9)	7,0-8,1 (40,4-34,9)
	Medium	l/100km (mpg)	5,2-5,8 (54,3-48,7)	5,6-6,2 (50,4-45,6)
	High	l/100km (mpg)	4,2-4,8 (67,3-58,9)	4,7-5,1 (60,1-55,4)
	Extra High	l/100km (mpg)	4,9-5,6 (57,6-50,4)	5,2-5,7 (54,3-49,6)
	Combined	l/100km (mpg)	5,0-5,5 (56,5-51,4)	5,4-5,9 (52,3-47,9)
WLTP CO <sub>2</sub> Emissions	Low	(g/km)	169-180	183-212
	Medium	(g/km)	136-152	148-163
	High	(g/km)	111-126	124-133
	Extra High	(g/km)	128-146	137-150
	Combined	(g/km)	130-145	142-155

■ Standard.

\*The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub> and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted

# XF SALOON - TECHNICAL SPECIFICATION

<b>POWERTRAIN</b>	<b>P250</b>	<b>P300</b>
Transmission	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Rear Wheel Drive (RWD)	RWD	AWD
Maximum power (PS (kW) / rpm)	250 (184) / 5.500	300 (221) / 5.500
Maximum torque (Nm / rpm)	365 / 1.300-4.500	400 / 1.500-4.500
Capacity (cc)	1.998	1.998
No. of cylinders / Valves per cylinder	4 / 4	4 / 4
Cylinder layout	Inline	Inline
Bore / stroke (mm)	83 / 92.3	83 / 92.3
Compression ratio (+/-0.5)	10.5	9.5
<b>PERFORMANCE</b>		
Acceleration (secs) 0-100 km/h (0-60mph)	6,9 (6,5)	6,1 (5,8)
Maximum speed km/h (mph)	250 (155)	250 (155)
<b>BRAKES</b>		
Front type	Single Piston Sliding Caliper, Vented Disc	Single Piston Sliding Caliper, Vented Disc
Front diameter (mm)	350	350
Rear type	Single Piston Sliding Caliper, Vented Disc	Single Piston Sliding Caliper, Vented Disc
Rear diameter (mm)	325	325
Park Brake	iEPB, motor on caliper	iEPB, motor on caliper

# XF SALOON - TECHNICAL SPECIFICATION

<b>WEIGHTS (kg)*</b>	<b>P250</b>	<b>P300</b>
Unladen weight (EU)**	1.735	1.819
Unladen weight (DIN)†	1.660	1.744
Gross Vehicle Weight (GVW)	2.290	2.370
<b>TOWING (kg)</b>		
Unbraked trailer	750	750
Maximum towing	1.900	1.900
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.190	4.270
<b>ROOF CARRYING (kg)</b>		
Maximum roof load (including cross bars)	75	75

\*Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

# XF SALOON - TECHNICAL SPECIFICATION

## FUEL ECONOMY

	P250	P300
Fuel tank capacity - useable litres	74	74
Diesel / Gasoline Particulate Filter (DPF / GPF)	■	■

## WLTP\*

Driveline			RWD	AWD
WLTP Consumption	Low	l/100km (mpg)	11,4-11,9 (24,8-23,7)	12,0-12,5 (23,5-22,6)
	Medium	l/100km (mpg)	7,9-8,5 (35,8-33,2)	8,6-9,1 (32,8-31,0)
	High	l/100km (mpg)	6,7-7,2 (42,2-39,2)	7,3-7,7 (38,7-36,7)
	Extra High	l/100km (mpg)	7,2-8,0 (39,2-35,3)	7,8-8,5 (36,2-33,2)
	Combined	l/100km (mpg)	7,7-8,4 (36,7-33,6)	8,4-8,9 (33,6-31,7)
WLTP CO <sub>2</sub> Emissions	Low	(g/km)	261-271	275-285
	Medium	(g/km)	180-193	196-207
	High	(g/km)	152-164	165-175
	Extra High	(g/km)	164-182	178-193
	Combined	(g/km)	177-191	191-203

■ Standard.

\*The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub> and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

# XF SPORTBRAKE - TECHNICAL SPECIFICATION

<b>POWERTRAIN</b>	<b>D200 MHEV</b>	
Transmission	Automatic	
Driveline: All Wheel Drive (AWD) or Rear Wheel Drive (RWD)	RWD	AWD
Maximum power (PS (kW) / rpm)	204 (150) / 3.750	204 (150) / 3.750
Maximum torque (Nm / rpm)	430 / 1.750-2.500	430 / 1.750-2.500
Capacity (cc)	1.998	1.998
No. of cylinders / Valves per cylinder	4 / 4	4 / 4
Cylinder layout	Inline	Inline
Bore / stroke (mm)	83 / 92,3	83 / 92,3
Compression ratio (+/-0.5)	16,5	16,5
<b>PERFORMANCE</b>		
Acceleration (secs) 0-100 km/h (0-60mph)	7,8 (7,3)	8,0 (7,5)
Maximum speed km/h (mph)	230 (143)	230 (143)
<b>BRAKES</b>		
Front type	Single Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	325	325
Rear type	Single Piston Sliding Caliper, Vented Disc	
Rear diameter (mm)	325	325
Park Brake	iEPB, motor on caliper	



# XF SPORTBRAKE - TECHNICAL SPECIFICATION

<b>WEIGHTS (kg)*</b>	<b>D200 MHEV</b>	
Unladen weight (EU)**	1.870	1.931
Unladen weight (DIN)†	1.795	1.856
Gross Vehicle Weight (GVW)	2.390	2.450
<b>TOWING (kg)</b>		
Unbraked trailer	750	750
Maximum towing	2.000	2.000
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.390	4.450
<b>ROOF CARRYING (kg)</b>		
Maximum roof load (including cross bars)	75	75

\*Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

# XF SPORTBRAKE - TECHNICAL SPECIFICATION

## FUEL ECONOMY

Fuel tank capacity - useable litres	<b>D200 MHEV</b>	68
Diesel / Gasoline Particulate Filter (DPF / GPF)		■

## WLTP\*

Driveline			RWD	AWD
WLTP Consumption	Low	l/100km (mpg)	6,6-6,9 (42,8-40,9)	7,3-8,3 (38,7-34,0)
	Medium	l/100km (mpg)	5,4-5,9 (52,3-47,9)	5,8-6,3 (48,7-44,8)
	High	l/100km (mpg)	4,5-5,0 (62,8-56,5)	4,9-5,2 (57,6-54,3)
	Extra High	l/100km (mpg)	5,3-5,8 (53,3-48,7)	5,5-5,9 (51,4-47,9)
	Combined	l/100km (mpg)	5,2-5,7 (54,3-49,6)	5,7-6,1 (49,6-46,3)
WLTP CO <sub>2</sub> Emissions	Low	(g/km)	172-182	192-217
	Medium	(g/km)	141-155	153-166
	High	(g/km)	117-130	128-136
	Extra High	(g/km)	138-152	145-155
	Combined	(g/km)	137-150	148-160

■ Standard.

\*The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub> and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

# XF SPORTBRAKE - TECHNICAL SPECIFICATION

<b>POWERTRAIN</b>	<b>P250</b>	<b>P300</b>
Transmission	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Rear Wheel Drive (RWD)	RWD	AWD
Maximum power (PS (kW) / rpm)	250 (184) / 5.500	300 (221) / 5.500
Maximum torque (Nm / rpm)	365 / 1.300-4.500	400 / 1.500-4.500
Capacity (cc)	1.998	1.998
No. of cylinders / Valves per cylinder	4 / 4	4 / 4
Cylinder layout	Inline	Inline
Bore / stroke (mm)	83 / 92,3	83 / 92,3
Compression ratio (+/-0.5)	10,5	9,5
<b>PERFORMANCE</b>		
Acceleration (secs) 0-100 km/h (0-60mph)	7,1 (6,7)	6,2 (5,9)
Maximum speed km/h (mph)	241 (150)	250 (155)
<b>BRAKES</b>		
Front type	Single Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	350	350
Rear type	Single Piston Sliding Caliper, Vented Disc	
Rear diameter (mm)	325	325
Park Brake	iEPB, motor on caliper	

# XF SPORTBRAKE - TECHNICAL SPECIFICATION

<b>WEIGHTS (kg)*</b>	<b>P250</b>	<b>P300</b>
Unladen weight (EU)**	1.801	1.880
Unladen weight (DIN)†	1.726	1.805
Gross Vehicle Weight (GVW)	2.330	2.400
<b>TOWING (kg)</b>		
Unbraked trailer	750	750
Maximum towing	1.900	1.900
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.230	4.300
<b>ROOF CARRYING (kg)</b>		
Maximum roof load (including cross bars)	75	75

\*Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

# XF SPORTBRAKE - TECHNICAL SPECIFICATION

## FUEL ECONOMY

	P250	P300
Fuel tank capacity - useable litres	74	74
Diesel / Gasoline Particulate Filter (DPF / GPF)	■	■

## WLTP\*

Driveline			RWD	AWD
WLTP Consumption	Low	l/100km (mpg)	11,6-12,0 (24,4-23,5)	12,2-12,6 (23,2-22,4)
	Medium	l/100km (mpg)	8,1-8,6 (34,9-32,8)	8,8-9,2 (32,1-30,7)
	High	l/100km (mpg)	6,9-7,4 (40,9-38,2)	7,5-7,8 (37,7-36,2)
	Extra High	l/100km (mpg)	7,6-8,3 (37,2-34,0)	8,2-8,7 (34,4-32,5)
	Combined	l/100km (mpg)	8,0-8,6 (35,3-32,8)	8,6-9,1 (32,8-31,0)
WLTP CO <sub>2</sub> Emissions	Low	(g/km)	264-274	279-287
	Medium	(g/km)	185-197	201-210
	High	(g/km)	158-168	170-178
	Extra High	(g/km)	174-189	187-199
	Combined	(g/km)	183-196	197-207

■ Standard.

\*The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub> and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

# XF SALOON - DIMENSIONS

**Vehicle Height** - 1.456mm

**Headroom**

Maximum headroom with / without  
Panoramic roof fitted

Front headroom 953mm / 991mm

Rear headroom 970mm / 970mm

**Vehicle Width**

With mirrors unfolded 2.089mm,

With mirrors folded 1.982mm

No mirrors 1.890mm

**Legroom**

Maximum front legroom 1.054mm

Maximum rear legroom 957mm

**Loadspace Capacity**

Height 687mm, Width 1.203mm

Loadspace width between arches 791mm

Maximum loadspace volume behind first row

Dry\* 1.128 litres, Wet\*\* 1.484 litres

Maximum loadspace volume behind second row

Dry\* 344 litres, Wet\*\* 459 litres

**Turning Circle**

Kerb-to-kerb 12,02m

Wall-to-wall 12,40m


Turns lock-to-lock 2,6



1.602mm



1.605mm



2.960mm

4.962mm

\*Dry: Volume as measured with VDA-compliant solid blocks (200mm x 50mm x 100mm).

\*\*Wet: Volume as measured by simulating the loadspace filled with liquid.

Dimensions were measured with vehicle at unladen weight.

# XF SPORTBRAKE - DIMENSIONS

**Vehicle Height** - 1.494mm

**Headroom**

Maximum headroom with / without  
Panoramic roof fitted

Front headroom 989mm / 991mm

Rear headroom 991mm / 994mm

**Vehicle Width**

With mirrors unfolded 2.089mm,

With mirrors folded 1.982mm

No mirrors 1.890mm

**Legroom**

Maximum front legroom 1.054mm

Maximum rear legroom 957mm

**Loadspace Capacity**

Height 635mm, Width 1.089mm

Loadspace width between arches 1.058mm

Maximum loadspace volume behind first row

Dry\* 1.342 litres, Wet\*\* 1.695 litres

Maximum loadspace volume behind second row

Dry\* 563 litres, Wet\*\* 716 litres

**Turning Circle**

Kerb-to-kerb 12,02m

Wall-to-wall 12,40m

Turns lock-to-lock 2,6



1.602mm



1.604mm



2.960mm

4.964mm

\*Dry: Volume as measured with VDA-compliant solid blocks (200mm x 50mm x 100mm).

\*\*Wet: Volume as measured by simulating the loadspace filled with liquid.

Dimensions were measured with vehicle at unladen weight.